

The AGNI-Wrap 50[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
<ul style="list-style-type: none"> • Min. 1 x layer of 13mm plasterboard on each side • Min 90mm solid or hollow masonry/concrete wall <ul style="list-style-type: none"> • Min. 1 x layer of 13mm plasterboard on each side • Min 90mm solid or hollow masonry/concrete wall 	PVC-U pipes				
	DN40mm PVC-U pipe	-/60/60	AGNI-Seal AGNI-Strap	AP-074	AP-074
	DN50mm PVC-U pipe	-/60/60	AGNI-Seal AGNI-Strap	AP-074	AP-074
	DN65mm PVC-U pipe	-/60/60	AGNI-Seal AGNI-Strap	AP-074	AP-074
	DN80mm PVC-U pipe	-/60/60	AGNI-Seal AGNI-Strap	AP-074	AP-074
	PEX Pipes				
	DN16mm PEX pipe	-/60/60	AGNI-Seal	AP-075	PF24069
	DN20mm PEX pipe	-/60/60	AGNI-Black	AP-234	PF25042
	DN25mm PEX pipe	-/60/60	AGNI-Seal	AP-075	PF24069
	DN25mm PEX pipe FIRE SIDE ONLY	-/60/60	AGNI-Seal AGNI-Strap	AP-073	PF24068
	DN32mm PEX pipe	-/60/60	AGNI-Black	AP-234	PF25042
	DN40mm PEX pipe	-/60/-	AGNI-Seal AGNI-Strap	AP-075	PF24078
	PVC-U conduit pipes				
	DN25mm flexible conduit filled with 3 x TPS cables	-/60/60	AGNI-Seal AGNI-Strap	AE-079	PF24078

The AGNI-Wrap 50[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
HVAC					
<ul style="list-style-type: none"> • Min. 1 x layer of 13mm plasterboard on each side • Min 90mm solid or hollow masonry/concrete wall 	1 x PE pair coil + 1 x TPS cable (BOTH SIDES)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
	1 x PE pair coil + 1 x TPS cable (FIRE SIDE ONLY)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
	1 x PE pair coil + 1 x TPS cable (NON-FIRE SIDE ONLY)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
	2 x PE pair coil + 2 x TPS cables (BOTH SIDES)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
	2 x PE pair coil + 2 x TPS cable (FIRE SIDE ONLY)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
	2 x PE pair coil + 2 x TPS cable (NON-FIRE SIDE ONLY)	-/60/60	AGNI-Black AGNI-Seal	AE-131	PF24102
PVC-U pipes					
<ul style="list-style-type: none"> • Min. 2 x layers of 13mm plasterboard on each side & 64mm steel/timber stud • Min 116mm solid or hollow masonry/concrete wall 	DN40mm PVC-U pipe	-/120/120	AGNI-Seal	AP-097	PF24081
	DN50mm PVC-U pipe	-/120/120	AGNI-Seal	AP-097	PF24100
	DN65mm PVC-U pipe	-/120/120	AGNI-Seal	AP-097	PF24100
	DN80mm PVC-U pipe	-/120/120	AGNI-Seal	AP-097	PF24100
	DN100 PVC-U pipe	-/120/120	AGNI-Seal	AP-097	PF24100

The AGNI-Wrap 50[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
<ul style="list-style-type: none"> • Min. 2 x layers of 13mm plasterboard on each side & 64mm steel/timber stud • Min 116mm solid or hollow masonry/concrete wall 	PEX pipes				
	DN16mm PEX pipe	-/120/120	AGNI-Seal	AP-099	PF24100
	DN20mm PEX pipe	-/120/120	AGNI-Seal	AP-099	PF25050
	DN25mm PEX pipe	-/120/120	AGNI-Seal	AP-099	PF24081
	DN40mm PEX pipe	-/120/45	AGNI-Seal	AP-099	PF24097
	PEX-AL-PEX pipes				
	DN20mm PEX-AL-PEX	-/120/120	AGNI-Seal	AP-100	PF24100
	PVC-U conduit pipes				
	DN50mm flexible conduit with 9 x TPS cables	-/120/120	AGNI-Seal	AE-098	PF24100
	DN25mm PVC-U conduit pipe with up to 8 x Optic cables	-/120/120	AGNI-Black	AE-187	PF25005
DN25mm flexible PVC-U conduit pipe with up to 6 x Optic cables	-/120/120	AGNI-Black	AE-187	PF25005	
<ul style="list-style-type: none"> • Min. 25mm Shaftliner & 1 x layer of 16mm FR plasterboard 	HVAC				
	1 x FR pair coil + TPS cable + 20mm condensate pipe	-/60/60	AGNI-Black	AE-185	PF24146
1 x PE pair coil + TPS cable + 20mm condensate pipe	-/60/60	AGNI-Black	AE-185	PF24146	

The AGNI-Wrap 50[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
• Min. 25mm Shaftliner & 1 x layer of 16mm FR plasterboard	PEX pipes				
	DN16mm PEX pipe	-/60/60	AGNI-Black	AP-210	PF25006
	DN20mm PEX pipe	-/60/60	AGNI-Black	AP-210	PF25006
	DN25mm PEX pipe	-/60/60	AGNI-Black	AP-210	PF24146
	PVC-U pipes				
	DN25mm PVC-U conduit with 3 x Data cables + 3 x Alarm cables + 3 x 4.8mm Optic cables	-/60/60	AGNI-Black	AE-212	PF25006
	DN25m PVC-U pipe	-/60/60	AGNI-Black	AP-213	PF25006
• Min 75mm Hebel wall	HVAC				
	1 x FR pair coil + TPS cable + 20mm condensate pipe	-/120/120	AGNI-Black	AE-173	PF24145
	1 x PE pair coil + TPS Cable + 20mm Condensate Pipe	-/120/60	AGNI-Black	AE-173	PF24145
	PEX pipes				
	DN25mm PEX pipe	-/60/60	AGNI-Black	AP-174	PF24145