

The AGNI-Black[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
<ul style="list-style-type: none"> • Min. 1 x layer of 13mm FR plasterboard on each side of the wall • Min 90mm concrete wall • Min 90mm masonry wall <ul style="list-style-type: none"> • Min. 1 x layer of 13mm FR plasterboard each side of the wall • Min 90mm concrete wall • Min 90mm masonry wall 	PEX pipes				
	DN16mm PEX pipe	-/60/60	-	AP-026	PF24143
	DN25mm PEX pipe	-/60/60	AGNI-Wrap	AP-234	PF25042
	DN25mm PEX pipe	-/60/45	-	AP-026	PF24143
	DN32mm PEX pipe	-/60/60	AGNI-Wrap	AP-234	PF25042
	DN32mm PEX pipe	-/60/15	-	AP-026	PF24143
	AC Bundles				
	1 x FR pair coil	-/60/60	-	AE141	PF24143
	1 x PE pair coil	-/60/45	-	AE141	PF24143
	FR pair coil + 1 x TPS cable + DN20 uPVC pipe	-/60/60	-	AE-143	PF24143
	1 x PE pair coil + 1 x TPS cable (BOTH SIDES)	-/60/60	AGNI-Seal	AE-131	PF24102
	1 x PE pair coil + 1 x TPS cable (FIRE SIDE ONLY)	-/60/60	AGNI-Seal	AE-131	PF24102
	1 x PE pair coil + 1 x TPS cable (NON-FIRE SIDE ONLY)	-/60/60	AGNI-Seal	AE-131	PF24102
	2 x PE pair coil + 2 x TPS cables (BOTH SIDES)	-/60/60	AGNI-Seal	AE-130	PF24102
2 x PE pair coil + 2 x TPS cable (FIRE SIDE ONLY)	-/60/60	AGNI-Seal	AE-130	PF24102	

The AGNI-Black[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
<ul style="list-style-type: none"> • Min. 1 x layer of 13mm FR plasterboard on each side of the wall • Min 90mm concrete wall • Min 90mm masonry wall 	2 x PE pair coil + 2 x TPS cable (NON-FIRE SIDE ONLY)	-/60/60	AGNI-Seal	AE-130	PF24102
	PEX-AL-PEX pipes				
	DN16mm PEX-AL—PEX pipe	-/60/60	-	AP-006	PF24143
	DN25mm PEX-AL—PEX pipe	-/60/60	-	AP-006	PF24143
	DN32mm PEX-AL—PEX pipe	-/60/60	-	AP-006	PF24143
	Electric cables				
	10 x TPS cables	-/60/60	-	AE-231	PF25042
	4.8MM Optic cable	-/60/60	-	AE-232	PF25042
	30mm Copper cable	-/60/60	-	AE-230	PF25042
	<ul style="list-style-type: none"> • 2 x layers of 13mm FR plasterboard wall on each side of the wall • Min 116mm concrete wall • Min 116mm masonry wall 	PEX pipes			
DN16mm PEX pipes		-/120/120	-	AP-112	PF24144
DN25mm PEX pipe		-/120/120	-	AP-112	PF24144
DN32mm PEX pipe		-/120/120	-	AP-112	PF24144
PEX-AL-PEX pipes					
DN16mm PEX-AL-PEX pipes		-/120/120	-	AP-113	PF24144
DN25mm PEX-AL-PEX pipes		-/120/120	-	AP-113	PF24144

The AGNI-Black[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
<ul style="list-style-type: none"> • 2 x layers of 13mm FR plasterboard wall on each side of the wall • Min 116mm concrete wall • Min 116mm masonry wall 	DN32mm PEX-AL-PEX pipes	-/120/120	-	AP-113	PF24144
	PEX-AL-PEX pipes				
	DN16mm PEX-AL-PEX pipes	-/120/120	-	AP-113	PF24144
	DN25mm PEX-AL-PEX pipes	-/120/120	-	AP-113	PF24144
	DN32mm PEX-AL-PEX pipes	-/120/120	-	AP-113	PF24144
	Polybutylene pipes (PB)				
	DN15mm PB pipe	-/120/120	-	AP-114	PF24101
	DN22mm PB pipe	-/120/120	-	AP-114	PF24101
	DN28mm PB pipe	-/120/120	-	AP-114	PF24101
	AC Bundles				
	1 x FR pair coil	-/120/120	-	AE-141	PF24144
	1 x PE pair coil	-/120/60	-	AP-114	PF24101
	1 x FR pair coil + electrical cable + DN25 uPVC pipe	-/120/120	-	AE-143	PF24144
	<ul style="list-style-type: none"> • Min 75mm Hebel wall 	AC Bundles			
1 x PE pair coil + TPS Cable + 20mm Condensate Pipe		-/120/60	AGNI-Wrap	AE-173	PF24145

The AGNI-Black[®] Application Range.

SUBSTRATE	SERVICE (s)	FRL	OTHER AGNI-PRODUCTS	AGNI-SYSTEM #	COMPLIANCE REFERENCE
• Min 75mm Hebel wall	1 x FR pair coil + TPS cable + 20mm condensate pipe	-/120/120	AGNI-Wrap	AE-173	PF24145
	PEX pipes				
	DN25mm PEX pipe	-/120/120	AGNI-Wrap	AP-174	PF24145
• Min. 25mm Shaftliner & 1 x layer of 16mm FR plasterboard wall • Min. 25mm Shaftliner & 1 x layer of 16mm FR plasterboard wall	AC Bundles				
	1 x FR pair coil + TPS cable + 20mm condensate pipe	-/60/60	AGNI-Wrap	AE-185	PF24146
	1 x PE pair coil + TPS cable + 20mm condensate pipe	-/60/60	AGNI-Wrap	AE-185	PF24146
	PEX pipes				
	DN16mm PEX pipe	-/60/60	AGNI-Wrap	AP-210	PF25006
	DN20mm PEX pipe	-/60/60	AGNI-Wrap	AP-210	PF25006
	DN25mm PEX pipe	-/60/60	AGNI-Wrap	AP-210	PF25006
	PVC-U conduit pipes				
	DN25mm uPVC rigid conduit filled with 3 x Data cables + 3 x Alarm cables + 3 x 4.8mm Optic cables	-/60/60	AGNI-Wrap	AP-212	PF25006
	PVC-U pipes				
	DN25mm PVC—U pipe	-/60/60	AGNI-Wrap	AP-213	PF25006